

**Subpart C—Related Requirements
for Outer Continental Shelf Fa-
cilities**

§ 254.40 Records.

You must make all records of services, personnel, and equipment provided by OSRO's or cooperatives available to any authorized BSEE representative upon request.

§ 254.41 Training your response personnel.

(a) You must ensure that the members of your spill-response operating team who are responsible for operating response equipment attend hands-on training classes at least annually. This training must include the deployment and operation of the response equipment they will use. Those responsible for supervising the team must be trained annually in directing the deployment and use of the response equipment.

(b) You must ensure that the spill-response management team, including the spill-response coordinator and alternates, receives annual training. This training must include instruction on:

- (1) Locations, intended use, deployment strategies, and the operational and logistical requirements of response equipment;
- (2) Spill reporting procedures;
- (3) Oil-spill trajectory analysis and predicting spill movement; and
- (4) Any other responsibilities the spill management team may have.

(c) You must ensure that the qualified individual is sufficiently trained to perform his or her duties.

(d) You must keep all training certificates and training attendance records at the location designated in your response plan for at least 2 years. They must be made available to any authorized BSEE representative upon request.

§ 254.42 Exercises for your response personnel and equipment.

(a) You must exercise your entire response plan at least once every 3 years (triennial exercise). You may satisfy this requirement by conducting separate exercises for individual parts of the plan over the 3-year period; you do

not have to exercise your entire response plan at one time.

(b) In satisfying the triennial exercise requirement, you must, at a minimum, conduct:

(1) An annual spill management team tabletop exercise. The exercise must test the spill management team's organization, communication, and decision making in managing a response. You must not reveal the spill scenario to team members before the exercise starts.

(2) An annual deployment exercise of response equipment identified in your plan that is staged at onshore locations. You must deploy and operate each type of equipment in each triennial period. However, it is not necessary to deploy and operate each individual piece of equipment.

(3) An annual notification exercise for each facility that is manned on a 24-hour basis. The exercise must test the ability of facility personnel to communicate pertinent information in a timely manner to the qualified individual.

(4) A semiannual deployment exercise of any response equipment which the BSEE Regional Supervisor requires an owner or operator to maintain at the facility or on dedicated vessels. You must deploy and operate each type of this equipment at least once each year. Each type need not be deployed and operated at each exercise.

(c) During your exercises, you must simulate conditions in the area of operations, including seasonal weather variations, to the extent practicable. The exercises must cover a range of scenarios over the 3-year exercise period, simulating responses to large continuous spills, spills of short duration and limited volume, and your worst case discharge scenario.

(d) BSEE will recognize and give credit for any documented exercise conducted that satisfies some part of the required triennial exercise. You will receive this credit whether the owner or operator, an OSRO, or a Government regulatory agency initiates the exercise. BSEE will give you credit for an actual spill response if you evaluate the response and generate a proper record. Exercise documentation

should include the following information:

- (1) Type of exercise;
- (2) Date and time of the exercise;
- (3) Description of the exercise;
- (4) Objectives met; and
- (5) Lessons learned.

(e) All records of spill-response exercises must be maintained for the complete 3-year exercise cycle. Records should be maintained at the facility or at a corporate location designated in the plan. Records showing that OSRO's and oil spill removal cooperatives have deployed each type of equipment also must be maintained for the 3-year cycle.

(f) You must inform the Regional Supervisor of the date of any exercise required by paragraph (b)(1), (2), or (4) of this section at least 30 days before the exercise. This will allow BSEE personnel the opportunity to witness any exercises.

(g) The Regional Supervisor periodically will initiate unannounced drills to test the spill response preparedness of owners and operators.

(h) The Regional Supervisor may require changes in the frequency or location of the required exercises, equipment to be deployed and operated, or deployment procedures or strategies. The Regional Supervisor may evaluate the results of the exercises and advise the owner or operator of any needed changes in response equipment, procedures, or strategies.

(i) Compliance with the National Preparedness for Response Exercise Program (PREP) Guidelines will satisfy the exercise requirements of this section. Copies of the PREP document may be obtained from the Regional Supervisor.

§ 254.43 Maintenance and periodic inspection of response equipment.

(a) You must ensure that the response equipment listed in your response plan is inspected at least monthly and is maintained, as necessary, to ensure optimal performance.

(b) You must ensure that records of the inspections and the maintenance activities are kept for at least 2 years and are made available to any authorized BSEE representative upon request.

§ 254.44 Calculating response equipment effective daily recovery capacities.

(a) You are required by § 254.26(d)(1) to calculate the effective daily recovery capacity of the response equipment identified in your response plan that you would use to contain and recover your worst case discharge. You must calculate the effective daily recovery capacity of the equipment by multiplying the manufacturer's rated throughput capacity over a 24-hour period by 20 percent. This 20 percent efficiency factor takes into account the limitations of the recovery operations due to available daylight, sea state, temperature, viscosity, and emulsification of the oil being recovered. You must use this calculated rate to determine if you have sufficient recovery capacity to respond to your worst case discharge scenario.

(b) If you want to use a different efficiency factor for specific oil recovery devices, you must submit evidence to substantiate that efficiency factor. Adequate evidence includes verified performance data measured during actual spills or test data gathered according to the provisions of § 254.45(b) and (c).

§ 254.45 Verifying the capabilities of your response equipment.

(a) The Regional Supervisor may require performance testing of any spill-response equipment listed in your response plan to verify its capabilities if the equipment:

- (1) Has been modified;
- (2) Has been damaged and repaired; or
- (3) Has a claimed effective daily recovery capacity that is inconsistent with data otherwise available to BSEE.

(b) You must conduct any required performance testing of booms in accordance with BSEE-approved test criteria. You may use the document "Test Protocol for the Evaluation of Oil-Spill Containment Booms," available from BSEE, for guidance. Performance testing of skimmers also must be conducted in accordance with BSEE approved test criteria. You may use the document "Suggested Test Protocol for the Evaluation of Oil Spill Skimmers for the OCS," available from BSEE, for guidance.